### Contact No. 368



## **Change Notice**

## M, EB & MB2400 Series

# Discontinuation of AT618 LED & AT213 Bezel & Alternates AT617 LED & AT212 Bezel

Type of Change:

✓ Engineering✓ Part Number✓ Product✓ Appearance

The AT618 LED and AT213 Bezel used in M Series Rockers, EB Series Pushbuttons and MB2400 Series Pushbuttons will be discontinued. This will include the red, yellow and green LEDs for AT618. The AT213 Bezel accommodates two rectangular AT618 LEDs, and the alternate AT212 Bezel accommodates two round AT617 LEDs. The LED specifications table below compares the values between AT618 and AT617 LEDs. Page 2 shows differences between the discontinued bezel and LED, and the alternate bezel and LED, plus a table displaying the discontinued part numbers and alternate part numbers. The changes will effect both standard and custom switches.




MB2400 Series Pushbutton with alternate AT212 Bezel and AT617 LEDs

DIFFERENCES IN SPECIFICATIONS BETWEEN AT618 & AT617 LEDS								
Electrical specifications are determined at a basic temperature of 25°C. LED circuit is independent of switch operation.		Discontinued AT618 LED			Alternate AT617 LED			
		C	E	F	C	E	F	
Color		Red	Yellow	Green	Red	Yellow	Green	
Maximum Forward Current	$\mathbf{I}_{FM}$	25mA	30mA	25mA	30mA	30mA	30mA	
Typical Forward Current	I <sub>F</sub>	20mA	20mA	20mA	20mA	20mA	20mA	
Forward Voltage	V <sub>F</sub>	2.25V	2.1V	2.2V	2.1V	2.1V	2.2V	
		I <sub>F</sub> = 20mA	I <sub>F</sub> = 20mA	I <sub>F</sub> = 20mA	I <sub>F</sub> = 20mA	I <sub>F</sub> = 20mA	I <sub>F</sub> = 20mA	
Maximum Reverse Voltage	$V_{RM}$	5V	5V	5V	5V	5V	5V	
Current Reduction Rate Above 25°C	ΔI <sub>F</sub>	0.33mA/°C	0.40mA/°C	0.33mA/°C	0.40mA/°C	0.40mA/°C	0.40mA/°C	
Ambient Temperature Range		−25°C ~ +70°C		−15°C ~ +70°C				

#### **Notes**

- The LED circuit is isolated and requires an external power source.
- For best results and safe use of LEDs, the supply voltage should be more than the LED forward voltage. Also, an appropriately valued ballast resistor should be used. Without the ballast resistor, the LED will be damaged or destroyed. The resistor value can be calculated by using the formula shown here.



- There are no changes to the switches' external dimensions.
- Contact information is below if more details are needed.

#### **Effective Date**

Orders for the discontinued AT618 LED and the AT213 Bezel will be accepted through November 1, 2021. The end of sales date is November 1, 2021. Sales of AT617 LED and AT212 Bezel are ongoing.

#### NKK SWITCHES CO., LTD.

European Office:

Mergenthalerallee 10-12, 65760 Eschborn, Germany

Tel: +49 61 96 400 -189 (English, German)

www.nkkswitches.eu E-mail: contact@nkkswitches.eu


### Contact No. 368



## Change Notice

## M, EB & MB2400 Series

# Discontinuation of AT618 LED & AT213 Bezel & Alternates AT617 LED & AT212 Bezel



The illustrations above display the physical similarities and differences between the discontinued bezel and LED and the alternate bezel and LED. At right are the specific part numbers for each discontinued item and the corresponding alternate part numbers.

Discontinued Part No.	Alternate Part No.			
Bezel	Bezel			
AT213A	AT212A			
LED	LED			
AT618C	AT617C			
AT618E	AT617E			
AT618F	AT617F			

#### NKK SWITCHES CO., LTD.

**European Office:** 

Mergenthalerallee 10-12, 65760 Eschborn, Germany

Tel: +49 61 96 400 -189 (English, German)

www.nkkswitches.eu E-mail: contact@nkkswitches.eu